RHI200-DO Ring Light
DUAL OVERDRIVE™

T-slots for mounting

Aluminum housing

97 x 97 mm clear aperture

IP65 rated enclosure

5-pin M12 connector (Male)

The RHI200-DO is an OverDrive™ only light source meant to provide external illumination for logistics. The RHI200-DO is a high intensity ring light that can be used with long working distances and features optional mounting brackets for most major machine vision cameras.

Warranty	Tested	Compliant	Rated	Connector
10 YEAR	IEC 62471	CE ROHS	IP 65	5-PIN M12

RHI200-DO HIGHLIGHTS

- ✔ Dual OverDrive features Deca OverDrive with 10x standard light output.
- ✔ Direct connect and control through camera's trigger output.
- ✔ Built for high speed conveyor systems.
- ✔ Compatible with most common major machine vision cameras.
- ✔ Designed for use with a polarizer.

DUAL OVERDRIVE

REV 09/24/24

SPECIFICATIONS

	Deca OverDrive Operation	Standard OverDrive™ Operation
Electrical Input	24 VDC +/- 5%	
Input Current	1.77 A average max. | Peak 2.3 A charge rate	
Input Power	42.5 W max.	
PNP Trigger	2 mA @ 4 VDC | 7 mA @ 12 VDC | 13.4 @ 24 VDC	
NPN Trigger	9.9 mA @ Common (0VDC)	
Trigger Input	PNP > +3.3 VDC (24 VDC max.) to activate **or** NPN > GND (<1.4 VDC) to activate **(not both)**	
Mode Control	Connect pin 5 to 1-10 VDC (10 - 100% output); 24 VDC (Max)	
Strobe Duration	Min. 10 µs | Max. 1 ms[1]	Beginning at 1 ms[1] | Max. 3 ms
Strobe Trigger Latency	6 µs	
Strobe Frequency	Max 4 kHz or 1 / Duty Cycle as calculated, whichever is less.[2]	
Duty Cycle	3%[2]	
Analog Intensity	The output is adjustable from 50% - 100% of intensity limit by a 1 - 9 VDC signal. Jumpering pin 5 to pin 1 will provide maximum intensity.	Not applicable
Connection	5-pin M12 connector	
Operating Temperature	-10° - 40° C (14° - 104° F) | RH max 80% non-condensing humidity	
Storage Temperature	-20° to 70° C (-4° to 158° F) | RH max 80% non-condensing humidity	
IP Rating	IP65	
Weight	3.7 lbs | 1.6 kg	
Compliances (Pending)	CE, IEC-62471, RoHS, UL, CSA, FCC, KCC Pending	
Warranty	10 years[3]	

[1] The RHI200-DO operates in Dual OverDrive™ from 25 µs to 1 ms. After 1 ms, standard OverDrive™ turns on. See page 6 for more information.
[2]See page 6 for more information.
[3]See SmartVisionLights.com/warranty for details.

WIRING CONFIGURATION

OVERDRIVE™ OPERATION MODE



Pin layout for light (Male Connector)

Pins	Function	Signal	Wire Color
1	Power In	+24VDC	BROWN
2	NPN	Sinking Signal	WHITE
3	GND	Ground	BLUE
4	PNP	Sourcing Signal	BLACK
5	Intensity Control	1-10VDC	GREY*

For maximum intensity, tie pin 5 to pin 1 at +24VDC.

For proper light function, apply either a PNP or NPN signal, not both.

Failure to supply light with correct input current will result in inconsistent lighting behavior.
(see Product Specifications for requirements)

LIGHTING PATTERNS

Smart Vision Lights recommends the RHI200-DO be used at a working distance between 500 mm to 2000 mm. **Illuminance values taken on white light - 5700K**

10° lighting patterns





14° lighting patterns





LIGHTING PATTERNS (continued)

Smart Vision Lights recommends the RHI200-DO be used at a working distance between 500 mm to 2000 mm. **Illuminance values taken on white light - 5700K**

30° lighting patterns





BEAM PATTERNS

Smart Vision Lights recommends the RHI200-DO be used at a working distance between 300 mm to 1500 mm. **Illuminance values taken on white light - 5700K**

10° lighting patterns



750 mm working distance | 1200 mm working distance | 1500 mm working distance

14° lighting patterns



500 mm working distance | 1000 mm working distance | 1200 mm working distance

BEAM PATTERNS (continued)

Smart Vision Lights recommends the RHI200-DO be used at a working distance between 300 mm to 1500 mm. **Illuminance values taken on white light - 5700K**

30° lighting patterns

600 mm



300 mm working distance



750 mm working distance



1000 mm working distance

LENS OPTICS

NARROW
Narrow, 10° angle-cone lenses create a narrow beam of illumination and are used for the longest working distances.

WIDE
Wide, 30° angle-cone lenses create the largest area of illumination. They create a floodlight effect and can be used for the shortest working distances.



NARROW (Standard)
Narrow, 14° angle-cone lenses create are standard. They create a narrow beam of illumination and are used for long working distances.

MOUNTING

T-Slots are located along the sides of the RHI200-DO.

The RHI200-DO comes with two M8-1.25 x 12 mm screws and two M8 x 1.25 T-nuts.

T-slots for mounting



EYE SAFETY

According to IEC 62471:2006. Full documentation available upon request with purchase of product.

Notice

Exempt Group: No photobiological hazard to eyes or skin even for continuous, unrestricted use. Applicable for wavelength 625.

Caution

Risk Group 1: Possibly hazardous optical radiation emitted from this product. Do not stare at operating lamp. May be harmful to eyes. Safe for most applications except prolonged exposure. Applicable for wavelength WHI.

ILLUMINATION

The RHI200-DO works best for:


Bright Field


Direct Lighting

DUTY CYCLE

Dual OverDrive lights will always begin the first 1 ms of operation in Deca OverDrive, followed by a shift down to Standard OverDrive for the remaining trigger, up to an additional 3 ms maximum.



The duty cycle of Dual OverDrive on the RHI200-DO Series is 3%.

To calculate the lockout period, use the following formula:

$$\frac{\textit{Strobe Duration}}{\textit{Duty Cycle}} - \textit{Strobe Duration} = \textit{Lockout Period}$$

Example: $\frac{25\ \mu s}{.03} - 25\ \mu s = 808\ \mu s$ *Lockout Period*

To calculate the strobes per second, use the following formula:

$$\frac{\textit{Duty Cycle}}{\textit{Strobe Duration (in seconds)}} = \textit{Strobes Per Second}$$

Example: $\frac{.03}{.000025\ sec} = 1{,}200$ *Strobes Per Second*

SAFESTROBE™

SafeStrobe™ is a unique technology that applies safe working parameters to ensure high current LEDs are not damaged by driving them beyond their limits, such as maximum strobe time or duty cycle. This is especially beneficial for overdriving our high current LEDs.

DUAL OVERDRIVE

Dual OverDrive provides both standard OverDrive™ and Deca OverDrive modes from a single integrated driver. Users can select the lighting mode via the strobe duration. Dual OverDrive will always begin with 1 ms of Deca OverDrive, followed by Standard OverDrive™.

Deca OverDrive provides up to 10x the amount of output as traditional continuous operation.

DUAL OVERDRIVE

HIDDEN STROBE™

Hidden Strobe works best in applications with short exposure times and a high repetition rate. As the rest period increases, and / or the frequency decreases, some strobing effects may become noticeable. This is due to the nature of overdrive, as all overdrive lights must have a period of rest called the duty cycle. However, the strobe effect will **always** be less noticeable in a light featuring Hidden Strobe than in a light without it.

Human vision is complex and highly circumstantial. There is no one-size-fits-all solution for maximizing the effect of Hidden Strobe™. However, setting the strobe duration to 1 ms or less is a good starting point that will work in many cases.

HIDDEN strobe

PART NUMBER GUIDE

RHI200-DO – □□ – □□□ – □□□ – □□□

HIDDEN STROBE™:
Leave blank for none
HS = Hidden Strobe™

COLOR:
WHI 625

LENS:
N14 = Narrow (14°, Standard)
N10 = Narrow (10)
W30 = Wide (30°)

LINEAR POLARIZER:
Leave blank for none
LPI = Factory Installed

Part Number Examples:

RHI200-DO-625	RHI200-DO, 625 nm Red Wavelength, Standard Lens Configuration
RHI200-DO-WHI-W30-LPI	RHI200-DO, White Wavelength, Wide Lens (30°), Linear Polarizer

Additional wavelengths and lens options available upon request.

ACCESSORIES

Power Cables

Lengths	Part Number
5 m	5PM12-5
10 m	5PM12-10
15 m	5PM12-15

Bracket



Description	Part Number
Mounting Bracket	BKT0036

Bracket



Description	Part Number
Mounting Bracket	BKT0037

Mounting Kit

Description	Part Number
M8-1.25 x12 mm screw	SC0030
M8 x 1.25 T-nut	NU009

Light comes with two screws and two T-nuts.

PRODUCT DRAWINGS

CAD files are available on our website. Drawings are in mm.



GLOSSARY

This glossary covers all Smart Vision Lights product families; some content in this section may not apply to this specific light.

TERMINOLOGY

Continuous Operation The light stays on continuously.
OverDrive™ Integrated driver that produces a high-current strobe to the LEDs to drive them beyond their nominal continuous operation output.
Multi-Drive™ Integrated driver that combines continuous operation and OverDrive™ strobe mode
NanoDrive™ Integrated driver that provides fast switching where the light can go from off to on in less than 500 ns.
Built-in Driver The driver contained within the light that controls the current to the LEDs and provides PNP, NPN, and analog dimming controls.
SmartVisionLink™ Integrated feature that enables lighting control through the Bluetooth module and app.
Camera to Light Connect the light directly to the camera, without the need for additional controllers or equipment.
Polarizers Filters that reduce reflections on specular surfaces.
Diffusers Widens the angle of emission by scattering light in all directions.
Pattern Area Lighting Modulated lighting pattern placed over a backlight's surface used to enhance defect detection on transparent and glossy surfaces
SafeStrobe Limiter to keep the light in safe working parameters.
Direct Connect Connect lights in a series without the use of cables.
Daisy-Chain Connect lights in a series with the use of cables.

TYPES OF ILLUMINATION


Projector


Dark Field


Radial


Bright Field


Direct


Axial


Line


Diffuse Panel


Backlight


Dome
"Light Tent"

COMMON COLOR / WAVELENGTHS LEGEND

Wavelengths options range from 365 nm to 1650 nm.*
Additional wavelengths available for many light families.



See Part Number section for **this light's available standard wavelengths.*

SWIR SHORT WAVE INFRARED

Shortwave Infrared LEDs are available in 1050 nm, 1200 nm, 1300 nm, 1450 nm, 1550 nm, and 1650 nm.*

Check Part Number section to see if **this light is available in SWIR wavelengths.*

ASR American Systems Registrar
ANAB ANSI National Accreditation Board ACCREDITED ISO/IEC 17021-1 MANAGEMENT SYSTEMS CERTIFICATION BODY
ISO 9001:2015 Certified QMS

US Office +1 (231) 722-1199
UK Office +44 (0) 1327 530000
smartvisionlights.com
info@smartvisionlights.com
sales@smartvisionlights.com

© Copyright 2024 Smart Vision Lights
This data sheet has been verified as accurate at the time of completion. It is subject to change without notification.